

# Bottom dischargers

A bottom discharger is a short belt conveyor that can swivel back and forth on its frame. Ideal for loading a planting machine or for use as an intermediate or soil conveyor. The bottom discharger has double cylinders as standard, a 65 cm wide chevron belt and an angle at the head end.



	Cermax 400	Cermax 500	Cermax 600	Cermax 700
Length	4.2 m	5.3 m	6.4 m	7 m
Max. height	2.2 m	2.8 m	3.2 m	3.6 m
Swivel range	2.45 m	2.75 m	3.2 m	3.3 m
Overhang	1.6 m	2.35 m	2.9 m	3.45 m

**CERMAX**



**Transporttechniek**

[www.cermax.nl](http://www.cermax.nl)

Lange Heerenstraat 46A | 4507 BB Schoondijke  
| The Netherlands | Tel. +31(0)117-769023 |  
info@cermax.nl



## Features

- Rubber chevron belt with high flights
- Large drive drums
- Large, robust infeed hopper
- Continuously adjustable belt speed
- Large 14" wheels for road transport
- Belt does not stop during hydraulic height adjustment
- Equipped with two cylinders for greater stability
- Two-component paint

## Versions

- Only hydraulically driven adjustment with valve block
- Only electrically driven by a one- or two-speed motor
- Electro-hydraulically driven by a hydraulic power unit

## General options

- Belt with curved, full-width flights (instead of standard chevron belt)
- Hydraulic swivelling, with the exception of type 400 (recommended)
- Electric swivelling
- Sprayed in different colour
- Variable-frequency drive
- Two-speed motor
- Large 15" wheels with five-hole hubs, rather than 14" wheels
- On both sides of the belt the valve block control (recommended)
- Radio remote control, along with electric valves with three functions
- Ball valve at the head end to stop the conveyor
- Additional folding support wheel (recommended)
- Two-stage fall breaker at the discharge end
- Driving lights at the head end of the conveyor with a truncated warning triangle



**Option:** : valve block control on both sides of the belt



**Version:** electro-hydraulically driven by a hydraulic power unit



**Version:** only electrically driven, variable-frequency drive

# CERMAX



## Transporttechniek

[www.cermax.nl](http://www.cermax.nl)

Lange Heerenstraat 46A | 4507 BB Schoondijke  
| The Netherlands | Tel. +31(0)117-769023 |  
info@cermax.nl