B-class conveyor

The B-class line is Cermax's basic belt conveyor. This conveyor can be used for anything, thanks to its simple operation and robust frame. This conveyor has a high chevron as standard, and is height adjustable through the use of two lift cylinders and a hand-operated pump. The belt motor has one speed and is supplied as standard with a 10 metre long cable with a phase change plug.



	Cermax B500	Cermax B600	Cermax B700	Cermax B800	Cermax B900
Length	5 m	6 m	7 m	8 m	8 m
Max. height	2.8 m	3.2 m	3.6 m	4 m	4.2 m
Overhang	1.4 m	1.6 m	3.5 m	4 m	4.3 m



www.cermax.nl

Lange Heerenstraat 46A | 4507 BB Schoondijke | The Netherlands | Tel. 0117-769023 | info@cermax.nl

Features

- Large capacity / competitively priced
- Rubber chevron belt with high flights
- Plug&play
- Large, robust infeed hopper
- Available with 65 or 80 cm width
- Simple construction
- With or without angled end
- Hydraulic height adjustment with hand-operated pump
- One speed; 50 m/min gear motor
- Two-component paint

General options

- Van de Graaf brand drum motor instead of a one-speed gear motor
- Belt with curved, full-width flights (instead of standard chevron belt)
- Two-speed motor
- Variable-frequency drive
- Hydraulic power unit with valve block
- Main wheels that can turn perpendicular to conveyor
- Sprayed in different colour
- Mechanical infeed height adjustment (50 cm)
- 2x swivel castors, industrial type



Option: mechanical infeed height adjustment



Option: variable-frequency drive, sprayed in a different colour



Option: hydraulic power unit with valve block, sprayed in a different colour



Option: belt with curved, full-width flights (instead of standard chevron belt)



www.cermax.nl

Lange Heerenstraat 46A | 4507 BB Schoondijke | The Netherlands | Tel. 0117-769023 | info@cermax.nl